

AXIAL

tracker **TWIN**



**POWERING THE FUTURE
OF SOLAR TRACKING**



BASIC SPECS

TRACKING SYSYEM:	HORIZONTAL AXIS E-W
COMMUNICATION:	ZIGBEE / RS485
SYSTEM VOLTAGE:	1000 VDC / 1500 VDC
TRACKING RANGE:	±55° AS STANDARD (UP TO ±60°)
DRIVE SYSTEM:	ENCLOSED SLEWING DRIVE DC MOTOR, 24 (24VDC)
POWER SULPLY:	SELF-POWERED
TEMPERATURE RANGE:	[-20,50] °C
INDEPENDENT ROWS:	SHARED TRANSMISSION EACH TWO ROWS
GCR:	TYPICAL RANGE 28% -50% , DEPENDING ON SITE CONDITIONS
TRACKING METHOD:	SOLAR ALGORITHM NREL SPA WITH 3DBACKTRACKING
OPERATIONAL WIND SPEED:	UP TO 70 KM/H
MAX WIND SPEED AT STOW POSTITION:	ACCORDING LOCAL STANDARD
ALLOWABLE SLOPE:	15%

KEY FEATURES

- **HIGHLY ADAPTATIVE AND SAFE**
- **EFFICENT AND SIMPLE FIELD INSTALLATION**
- **UP TO 70 KM/H OPERATIONAL WIND SPEED**
- **TEMPERATURA RANGE -20,50°C**
- **TRANSMISSION:** REDUCE CLEARANCE AND INCREASED ROTATION ACCURANCY IN THE TRANSMISSION COMPARED TO OTHER SYSTEMS
- **INCREASED EFFICIENCY BY SHARED TRANSMISSION EACH TWO TRACKERS:**THE POWER TO PRODUCE THE MOVEMENT OF BOTH TRACKERS IS GENERATED FROM ONE SINGLE MOTOR, BUT THE EFFECTS OF WIND LOADS ARE DISTRIBUTED BETWEEN BOTH STRUCTURES THROUGH INDEPENDENT SLEWING DRIVES

DIMENSIONS

CONFIGURATIONS*

CAPACITY:	2 STRINGS PER ROW. COMPATIBLE WITH MOST UTILITY SCALE PV MODULES
GROUND CLEARANCE:	1 m (55°) - 1,28 m. (0°) AS STANDARD

* Available in different configurations / Aproximate dimensions

WARRANTY

SLEWING DRIVE:	5 YEARS
ENGINE:	5 YEARS
ELECTRONICS:	10 YEARS
BATTERY:	UP TO 10 YEARS
STRUCTURAL WARRANTY:	UP TO 25 YEARS
CORROSION WARRANTY:	UP TO 25 YEARS



EN 1090-1
Factory
Production
Control

www.tuv.com
ID 9108642046



Sistema de
Gestión
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108642046

WIND DYNAMICS STUDIES
Tested in Wind Tunel
CFD Studies